

APPLICATORS



APPLICATORS

Rubber Expanding Applicators:
Used in round or square tubing for a tight fit. Rubber expands inside the tubing.

Pipe Plug Applicators:
These adaptors have a 1/2-13 threaded hole, so then can be used with a standard 37 or 46 series caster to adapt them for use with pipe fittings.

Made of heavy duty cold rolled steel with zinc plated finish. Please see chart below.

Rubber Expanding Applicators

Applicator Number	Tubing ID (Inches)	Size Range (Inches)	Parts in Applicator Kit				
			Knurled Nut	Expanding Rubber	Plain Bushing	Base Washer	
						Series 37	Series 50*
11	7/8	0.862-0.927	1435-02*	1645-00	1432-00	1427-02	1473-02
15	1-1/8	1.030-1.140	1436-02	1646-00	1433-00	1427-02	1473-02
17	1-3/16	1.178-1.303	1441-02	1648-00	1430-00	1427-02	1473-02
19C	1-3/8	1.360-1.425	1438-02*	1647-00	1436-00	1427-02	1473-02
19A	1-1/2	1.426-1.589	1437-02*	1649-00	1434-00	1427-02	1473-02
21	1-7/8	1.790-1.850	1422-02	1650-00	1440-00	1427-02	1473-02

Note: * Also available in stainless steel.



Pipe Plug Applicators

Applicator Number	Thread Size (NPT)
PIPEAPP-75	3/4"
PIPEAPP-10	1"
PIPEAPP-12	1-1/4"
PIPEAPP-1-14	1-14(straight thread)

GREASE SEAL & ZERK

FEATURES:

Grease Seals are recommended when it is important to keep out dirt and moisture. Grease seals help retain lubricant for easier swiveling and longer bearing life. They are made from materials that offer resistance to grease, oils, as well as various chemicals, and detergents.

ZERKS: These fittings help make maintenance and continued proper care of products easier. Making sure that the product has the correct lubrication is an essential part to making the product last longer for you!



ANGLED ZERK



ZERK



SERIES 40-47
Temperature Range:
275°F intermittent use.



SERIES 70S
Temperature Range:
275°F intermittent use.


BUMPERS

FEATURES:

1. **CORNER:** Corner bumper for mounting on flat surfaces. 7/8" thick x 1" high x 2-5/8" long from inside corner.
2. **DONUT:** 3-1/2" diameter bumper fits 1" O.D. round and square tubing.
3. **DISC:** 5" diameter rolling bumpers. Tapered grey PVC bonded to a zinc-plated insert with removable center bushings to fit diameters from 3/8" to 1-1/8".



1



2

BMPR 3.5DR



3

BMPR 5-10-4PK
BMPR 5-14

SPECIAL TOP PLATE

FEATURES:

CORNER TOP PLATE:

Suited for light duty casters.
Finished in a zinc plating finish.



CORNER TOP PLATE