

LIGHT DUTY CASTERS

23,24 Series

Zinc



4-23-201G-21 Zinc

STANDARD THREADED STEM SIZES	
Threaded Stem Number	Dimensions
21	1/2 - 13 × 1
22	1/2 - 13 × 1-1/2
23	1/2 - 13 × 2-3/4
24	3/8 - 16 × 1-1/2
43	7/16 - 14 × 1-1/2



4-24-201G-41 Zinc

STANDARD SPRING RING STEM SIZES	
Stem Number	Dimensions
41	.845 × 2-3/16
42	7/16 × 1-3/8
45	7/16 × 1-15/16

FEATURES:

- 1. Finish-**
Bright zinc plating.
- 2. Swivel-**
Double ball bearing with hardened raceways for extra strength.
- 3. Construction-**
Heavy duty gauge steel formed for extra strength.
- 4. Axle-**
5/16" dia. bolt with lock nut.
- 5. Brake-**
Side brake and Top Lock Brake available.

WHEELS:



BRAKES:



Dia.	Wheel			Cap.	Load Height	Swivel Radius	23 Series	24 Series	App. Wgt.
	TW	TYPE	Brg.				Threaded Stem	Spring Ring Stem	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
3	1	TPR/PP	Plain	125	3-5/8	2-3/4	3-23-201G	3-24-201G	1
	1	TPR/PP	Plain	125	3-5/8	2-3/4	3-23-301B	3-24-301B	1
	1	Pro-U Grey	Delrin	125	3-5/8	2-3/4	3-23-211P	3-24-211P	1
	1	Polyolefin	Plain	125	3-5/8	2-3/4	3-23-5110	3-24-5110	1
4	1	TPR/PP	Plain	150	4-5/8	3-5/16	4-23-201G	4-24-201G	1-1/4
	1	TPR/PP	Plain	150	4-5/8	3-5/16	4-23-301B	4-24-301B	1-1/4
	1	Pro-U Grey	Delrin	150	4-5/8	3-5/16	4-23-211P	4-24-211P	1-1/4
	1	Polyolefin	Plain	150	4-5/8	3-5/16	4-23-5110	4-24-5110	1-1/4
5	1	TPR/PP	Plain	150	5-5/8	4	5-23-201G	5-24-201G	1-1/4
	1	TPR/PP	Plain	150	5-5/8	4	5-23-301B	5-24-301B	1-1/4
	1	Pro-U Grey	Delrin	160	5-5/8	4	5-23-211P	5-24-211P	1-1/4
	1	Polyolefin	Plain	150	5-5/8	4	5-23-5110	5-24-5110	1-1/4

LIGHT DUTY CASTERS

35,36 Series

Zinc

FEATURES:

1. Finish- Bright zinc plating.
2. Swivel- Double ball bearing with hardened raceways for extra strength.
3. Rigid- Single piece pressed to form for extra strength.
4. Construction- Heavy duty gauge steel formed for extra strength.
5. Axle- 5/16" dia. bolt with lock nut.
6. Brake- Side brake and Top Lock Brake available for swivel.

WHEELS:



BRAKES:



4-35-201G-4 Zinc

STANDARD TOP PLATE SIZES			
Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2B	1-3/4 x 3	1 x 2-5/16	1/4
4	2-3/8 x 3-5/8	1-3/4 x 3	5/16



4-36-201G-4 Zinc

STANDARD TOP PLATE SIZE			
Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
4	2-3/8 x 3-5/8	1-3/4 x 3	5/16

Wheel				Cap.	Load Height	Swivel Radius	Series 35 Swivel Plate	Series 36 Rigid Plate	App. Wgt.
Dia.	TW	TYPE	Brg.						
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
3	1	TPR/PP	Plain	125	3-3/4	2-3/4	3-35-201G	3-36-201G	1
	1	TPR/PP	Plain	125	3-3/4	2-3/4	3-35-301B	3-36-301B	1
	1	Pro-U Grey	Delrin	125	3-3/4	2-3/4	3-35-211P	3-36-211P	1
	1	Polyolefin	Plain	125	3-3/4	2-3/4	3-35-5110	3-36-5110	1
4	1	TPR/PP	Plain	150	4-3/4	3-5/16	4-35-201G	4-36-201G	1-1/4
	1	TPR/PP	Plain	150	4-3/4	3-5/16	4-35-301B	4-36-301B	1-1/4
	1	Pro-U Grey	Delrin	150	4-3/4	3-5/16	4-35-211P	4-36-211P	1-1/4
	1	Polyolefin	Plain	150	4-3/4	3-5/16	4-35-5110	4-36-5110	1-1/4
5	1	TPR/PP	Plain	150	5-3/4	4	5-35-201G	5-36-201G	1-1/4
	1	TPR/PP	Plain	150	5-3/4	4	5-35-301B	5-36-301B	1-1/4
	1	Pro-U Grey	Delrin	160	5-3/4	4	5-35-211P	5-36-211P	1-1/4
	1	Polyolefin	Plain	150	5-3/4	4	5-35-5110	5-36-5110	1-1/4

LIGHT DUTY CASTERS

37 Series

Zinc



4-37-201G-21 Zinc

EXPANDING RUBBER APPLICATOR SIZES						
Applicator Number	Tubing ID (Inches)	Size Range (Inches)	Knurled Nut	Expanding Rubber	Plain Bushing	Base Washer
11	7/8	0.852-0.927	1435-02	1645-00	1432-00	1427-02
15	1-1/8	1.030-1.140	1436-02	1646-00	1433-00	1427-02
17	1-3/16	1.178-1.303	1441-02	1648-00	1430-00	1427-02
19C	1-3/8	1.360-1.425	1438-02	1647-00	1436-00	1427-02
19A	1-1/2	1.426-1.589	1437-02	1649-00	1434-00	1427-02
21	1-7/8	1.790-1.850	1422-02	1650-00	1440-00	1473-02

Wheel				Cap.	Load Height	Swivel Radius	Series 37 Applicator	App. Wgt.
Dia.	TW	TYPE	Brg.					
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Pounds
3	1	TPR/PP	Plain	125	3-5/8	2-3/4	3-37-201G	1
	1	TPR/PP	Plain	125	3-5/8	2-3/4	3-37-301B	1
	1	Pro-U Grey	Delrin	125	3-5/8	2-3/4	3-37-211P	1
	1	Polyolefin	Plain	125	3-5/8	2-3/4	3-37-5110	1
4	1	TPR/PP	Plain	150	4-5/8	3-5/16	4-37-201G	1-1/4
	1	TPR/PP	Plain	150	4-5/8	3-5/16	4-37-301B	1-1/4
	1	Pro-U Grey	Delrin	150	4-5/8	3-5/16	4-37-211P	1-1/4
	1	Polyolefin	Plain	150	4-5/8	3-5/16	4-37-5110	1-1/4
5	1	TPR/PP	Plain	150	5-5/8	4	5-37-201G	1-1/4
	1	TPR/PP	Plain	150	5-5/8	4	5-37-301B	1-1/4
	1	Pro-U Grey	Delrin	160	5-5/8	4	5-37-211P	1-1/4
	1	Polyolefin	Plain	150	5-5/8	4	5-37-5110	1-1/4

FEATURES:

1. Finish- Bright zinc plating.
2. Swivel- Double ball bearing with hardened raceways for extra strength.
3. Construction- Heavy duty gauge steel formed for extra strength.
4. Axle- 5/16" dia. bolt with lock nut.
5. Brake- Side brake and Top Lock Brake available.
6. Applicator- Fits a wide range of tubing from 7/8" I.D. to 1-7/8" I.D., round or square. Please specify exact tubing I.D. or O.D. and gauge.

WHEELS:



BRAKES:

