

PHENOLIC WHEELS

Heavy Duty



**421R
PHENOLIC**
Temperature Range: -4°F ~ 360°F



**420R
PHENOLIC**
Temperature Range: -4°F ~ 360°F

FEATURES:

These wheels are compression molded using phenolic resin.

They are a hard tread wheel and have a high load capacity. These wheels are resistant to most oils and chemicals.

They provide more protection to the floor than **Cast Iron wheels.**

They also have the advantage of rolling more smoothly while being quieter than steel wheels.

Wheel		Cap.	Bearing Bore	Hub Length	Bore Size Less Brg.	Catalog No.	App. Wgt.
Dia.	TW						
Ins.	Ins. Brg.	Pounds	Ins.	Ins.	Ins.		Pounds
4	2 Roller	700	3/4	2-3/8	1-3/16	4-420R	1-1/2
	2 Plain	700	3/4	2-3/16	3/4	4-421R	1-1/2
5	2 Roller	900	3/4	2-3/8	1-3/16	5-420R	1-3/4
	2 Plain	900	3/4	2-3/16	3/4	5-421R	1-3/4
6	2 Roller	900	3/4	2-3/8	1-3/16	6-420R	2-1/2
	2 Plain	900	3/4	2-3/16	3/4	6-421R	2-1/2
8	2 Roller	1000	3/4	2-3/8	1-3/16	8-420R	4
	2 Plain	1000	3/4	2-3/16	3/4	8-421R	4