

# PRO-U WHEELS

## Heavy Duty



**220P**

Temperature Range: -30°F ~ 180°F

Hardness: 95±5 shore A

### FEATURES:

Pro-U wheels are polyurethane tread mechanically molded to a polyolefin hub.

The extra thick hub allows this wheel to be used in applications where load and shock are important.

These wheels come with sealed roller bearings for normal use or Delrin bearings for corrosive environments. Standard colors are dark gray tread with lighter gray hubs.

### POLYURETHANE-GREY

Dia.	Wheel		Cap.	Bearing	Hub	Catalog No.	App.
	TW	Brg.					
Ins.	Ins.		Pounds	Ins.	Ins.		Pounds
4	2	Roller	600	3/4	2-3/8	4-220P	1
	2	Delrin	600	3/4	2-3/8	4-234P	3/4
5	1-1/2	Roller	500	3/4	2	5-250P	1-1/4
	2	Roller	700	3/4	2-3/8	5-220P	1-1/2
	2	Delrin	700	3/4	2-3/8	5-234P	1-1/4
6	1-1/2	Roller	600	3/4	2	6-250P	1-1/2
	2	Roller	800	3/4	2-3/8	6-220P	1-3/4
	2	Delrin	800	3/4	2-3/8	6-234P	1-1/2
8	1-1/2	Roller	800	3/4	2	8-250P	2
	1-1/2	Delrin	800	1/2	2	8-454P	1-3/4
	2	Roller	1000	3/4	2-3/8	8-220P	2-1/2
	2	Delrin	1000	3/4	2-3/8	8-234P	2-1/4
10	1-1/2	Ball	800	1/2	2	10-253P	2-3/4

Note: Precision Ball Bearing available.