

PRO-U WHEELS

Medium Duty



213P
Temperature Range:
 -30°F ~ 180°F
Hardness: 95±5 shore A

FEATURES:

Pro-U wheels are polyurethane tread mechanically molded to a Polyolefin hub.

These are molded with a precision ball bearing and fitted with plastic thread guards.

Standard colors are dark gray tread with lighter gray hubs. Blue Pro-U tread available by request.

These are very attractive all purpose wheels that are very durable and can be used in almost all environments.

POLYURETHANE-GREY

Wheel		Cap.	Bearing Bore	Hub Length	Catalog No.	App. Wgt.	
Dia.	TW						
Ins.	Ins. Brg.	Pounds	Ins.	Ins.		Pounds	
3	1	Delrin	125	5/16	1-1/4	3-211P	1/4
	1-1/4	Ball	250	1/2	1-5/8	3-213P	1/2
	1-1/4	Delrin	250	1/2	1-1/2	3-214P	1/2
3-1/2	1-1/4	Ball	250	3/8	1-5/8	3-1/2-213P	1/2
	1-1/4	Delrin	250	1/2	1-1/2	3-1/2-214P	1/2
4	1	Delrin	150	5/16	1-1/4	4-211P	1/2
	1-1/4	Ball	275	3/8	1-5/8	4-213P	1/2
	1-1/4	Delrin	275	1/2	1-1/2	4-214P	1/2
5	1	Delrin	160	5/16	1-1/4	5-211P	1/2
	1-1/4	Ball	300	3/8	1-5/8	5-213P	3/4
	1-1/4	Delrin	300	1/2	1-1/2	5-214P	3/4
6	1-1/4	Ball	300	3/8	1-5/8	6-213P	1
	1-1/4	Delrin	300	1/2	1-1/2	6-214P	1

Note: S.S Precision Ball Bearing is available.