

HEAVY DUTY CASTERS

60,61 Series Zinc

FEATURES:

1. Finish- Bright zinc plating.
2. Swivel-
Double ball bearing formed raceways for extra strength.
3. Rigid-
Welded with heavy duty gauge steel for extra strength.
4. Riveted King Pin-
5/8" dia.
5. Construction-
Formed from 1/4" thick steel for extra strength.
6. Grease Fittings-
Provided in swivel raceway and wheel bearings.
7. Axle-
1/2" dia. bolt with zerk and lock nut.
8. Brake + Lock-
Top Lock Brake, Swivel Lock and Pro Lock available for swivel.
9. Fork leg spacing 2-1/2".
10. Optional heat treated raceways and top plate.



6-60-220D-1 Zinc

| STANDARD TOP PLATE SIZE | | | |
|-------------------------|---------------|--|---------------|
| Top Plate Number | Overall Size | Bolt Hole Spacing | Mounting Bolt |
| 1 | 4 × 4-1/2 | 2-5/8 × 3-5/8 slotted to 3 × 3 | 3/8 |
| 3 | 4-1/2 × 6-1/4 | 2-7/16 × 4-15/16 slotted to 3-3/8 × 5-1/4 | 1/2 |



6-61-220D-1 Zinc

| STANDARD TOP PLATE SIZE | | | |
|-------------------------|---------------|--|---------------|
| Top Plate Number | Overall Size | Bolt Hole Spacing | Mounting Bolt |
| 1 | 4 × 4-1/2 | 2-5/8 × 3-5/8 slotted to 3 × 3 | 3/8 |
| 3 | 4-1/2 × 6-1/4 | 2-7/16 × 4-15/16 slotted to 3-3/8 × 5-1/4 | 1/2 |

WHEELS:



BRAKES:



| Dia. | Wheel | | | Cap. | Load Height | Swivel Radius | 60 Series | 61 Series | App. Wgt. |
|------|-------|-----------------|--------|--------|-------------|---------------|--------------|-------------|-----------|
| | TW | TYPE | Brg. | | | | Swivel Plate | Rigid Plate | |
| Ins. | Ins. | | | Pounds | Ins. | Ins. | Catalog No. | Catalog No. | Pounds |
| 4 | 2 | Pro-U Grey | Roller | 600 | 5-5/8 | 3-9/16 | 4-60-220P | 4-61-220P | 4 |
| | 2 | Easy Roll Flat | Roller | 350 | 5-5/8 | 3-9/16 | 4-60-220F | 4-61-220F | 4 |
| | 2 | Phenolic | Plain | 700 | 5-5/8 | 3-9/16 | 4-60-421R | 4-61-421R | 4 |
| | 2 | Phenolic | Roller | 700 | 5-5/8 | 3-9/16 | 4-60-420R | 4-61-420R | 4 |
| | 2 | Polyolefin | Roller | 500 | 5-5/8 | 3-9/16 | 4-60-5320 | 4-61-5320 | 4 |
| 5 | 2 | Pro-U Grey | Roller | 700 | 6-1/2 | 4-5/16 | 5-60-220P | 5-61-220P | 4 |
| | 2 | Easy Roll Donut | Roller | 450 | 6-1/2 | 4-5/16 | 5-60-220D | 5-61-220D | 4 |
| | 2 | Easy Roll Flat | Roller | 300 | 6-1/2 | 4-5/16 | 5-60-220F | 5-61-220F | 4 |
| | 2 | Phenolic | Plain | 900 | 6-1/2 | 4-5/16 | 5-60-421R | 5-61-421R | 4 |
| | 2 | Phenolic | Roller | 900 | 6-1/2 | 4-5/16 | 5-60-420R | 5-61-420R | 4 |
| 6 | 2 | Polyolefin | Roller | 650 | 6-1/2 | 4-5/16 | 5-60-5320 | 5-61-5320 | 4 |
| | 2 | Pro-U Grey | Roller | 800 | 7-1/2 | 5-1/16 | 6-60-220P | 6-61-220P | 4-1/2 |
| | 2 | Easy Roll Donut | Roller | 450 | 7-1/2 | 5-1/16 | 6-60-220D | 6-61-220D | 4-1/2 |
| | 2 | Easy Roll Flat | Roller | 600 | 7-1/2 | 5-1/16 | 6-60-220F | 6-61-220F | 4-1/2 |
| | 2 | Phenolic | Plain | 900 | 7-1/2 | 5-1/16 | 6-60-421R | 6-61-421R | 4-1/2 |
| 8 | 2 | Phenolic | Roller | 900 | 7-1/2 | 5-1/16 | 6-60-420R | 6-61-420R | 4-1/2 |
| | 2 | Polyolefin | Roller | 700 | 7-1/2 | 5-1/16 | 6-60-5320 | 6-61-5320 | 4-1/2 |
| | 2 | Pro-U Grey | Roller | 1000 | 9-1/2 | 6-1/2 | 8-60-220P | 8-61-220P | 5-1/2 |
| | 2 | Easy Roll Donut | Roller | 500 | 9-1/2 | 6-1/2 | 8-60-220D | 8-61-220D | 5-1/2 |
| | 2 | Easy Roll Flat | Roller | 675 | 9-1/2 | 6-1/2 | 8-60-220F | 8-61-220F | 5-1/2 |
| 8 | 2 | Phenolic | Plain | 1000 | 9-1/2 | 6-1/2 | 8-60-421R | 8-61-421R | 5-1/2 |
| | 2 | Phenolic | Roller | 1000 | 9-1/2 | 6-1/2 | 8-60-420R | 8-61-420R | 5-1/2 |
| | 2 | Polyolefin | Roller | 900 | 9-1/2 | 6-1/2 | 8-60-5320 | 8-61-5320 | 5-1/2 |