

MEDIUM DUTY CASTERS

40,41,42 Series
405,415,425 Series

Zinc
Nickel

FEATURES:

- 1. Finish-**
Bright zinc plating or
Bright nickel plating.
- 2. Swivel-**
Double ball bearing with
hardened raceways for extra
strength.
- 3. Rigid-**
Pressed or welded with heavy
duty gauge steel for extra
strength.
- 4. Dust Cover-**
Helps protect swivel bearings.
- 5. Construction-**
Heavy duty gauge steel formed
for extra strength.
- 6. Axle-** 3/8" dia. bolt with lock nut.
- 7. King Pin-**
1/2" steel rivet hydraulically
upset.
- 8. Brake-**
Both Top Lock Brake and Maxi
Lock Brake are available for
swivel.

Note: Many other plate sizes are
available upon request.
Contact the distributor for
more information.

WHEELS:



BRAKES:



5-40-213P-2 Zinc
5-405-213P-2 Nickel

STANDARD TOP PLATE SIZES

Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8



5-41-5130-2 Zinc
5-415-5130-2 Nickel

STANDARD TOP PLATE SIZE

Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16



5-42-214D-5 Zinc
5-425-214D-5 Nickel

STANDARD TOP PLATE SIZES

Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16
2A	2-1/2 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8

Dia.	Wheel			Cap.	Load Height	Swivel Radius	40 Series	41 Series	App. Wgt.
	TW	TYPE	Brg.				Swivel Plate	Pressed Rigid	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
3	1-1/4	Pro-U Grey	Ball	250	4-1/8	2-7/8	3-40-213P	3-41-213P	1-1/2
	1-1/4	Pro-U Grey	Delrin	250	4-1/8	2-7/8	3-40-214P	3-41-214P	1-1/2
	1-1/4	Easy Roll Donut	Ball	175	4-1/8	2-7/8	3-40-213D	3-41-213D	1-1/2
	1-1/4	Easy Roll Donut	Delrin	175	4-1/8	2-7/8	3-40-214D	3-41-214D	1-1/2
	1-1/4	Easy Roll Flat	Ball	200	4-1/8	2-7/8	3-40-213F	3-41-213F	1-1/2
	1-1/4	Easy Roll Flat	Delrin	200	4-1/8	2-7/8	3-40-214F	3-41-214F	1-1/2
	1-1/4	Polyolefin	Plain	250	4-1/8	2-7/8	3-40-5130	3-41-5130	1-1/2
	1-1/4	Pro-U Grey	Ball	250	4-5/8	3-1/4	3-1/2-40-213P	3-1/2-41-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	250	4-5/8	3-1/4	3-1/2-40-214P	3-1/2-41-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	225	4-5/8	3-1/4	3-1/2-40-213D	3-1/2-41-213D	1-3/4
3-1/2	1-1/4	Easy Roll Donut	Delrin	225	4-5/8	3-1/4	3-1/2-40-214D	3-1/2-41-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	250	4-5/8	3-1/4	3-1/2-40-213F	3-1/2-41-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	250	4-5/8	3-1/4	3-1/2-40-214F	3-1/2-41-214F	1-3/4
	1-1/4	Polyolefin	Plain	250	4-5/8	3-1/4	3-1/2-40-5130	3-1/2-41-5130	1-3/4
	1-1/4	Pro-U Grey	Ball	275	5-1/8	3-1/2	4-40-213P	4-41-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	275	5-1/8	3-1/2	4-40-214P	4-41-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	250	5-1/8	3-1/2	4-40-213D	4-41-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	250	5-1/8	3-1/2	4-40-214D	4-41-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	275	5-1/8	3-1/2	4-40-213F	4-41-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	275	5-1/8	3-1/2	4-40-214F	4-41-214F	1-3/4
4	1-1/4	Polyolefin	Plain	275	5-1/8	3-1/2	4-40-5130	4-41-5130	1-3/4
	1-1/4	Pro-U Grey	Ball	300	6-1/4	4	5-40-213P	5-41-213P	2
	1-1/4	Pro-U Grey	Delrin	300	6-1/4	4	5-40-214P	5-41-214P	2
	1-1/4	Easy Roll Donut	Ball	250	6-1/4	4	5-40-213D	5-41-213D	2
	1-1/4	Easy Roll Donut	Delrin	250	6-1/4	4	5-40-214D	5-41-214D	2
	1-1/4	Easy Roll Flat	Ball	300	6-1/4	4	5-40-213F	5-41-213F	2
	1-1/4	Easy Roll Flat	Delrin	300	6-1/4	4	5-40-214F	5-41-214F	2
	1-1/4	Polyolefin	Plain	300	6-1/4	4	5-40-5130	5-41-5130	2
	1-1/4	Pro-U Grey	Ball	300	7-1/4	4-1/2	6-40-213P	6-41-213P	2-1/4
	1-1/4	Pro-U Grey	Delrin	300	7-1/4	4-1/2	6-40-214P	6-41-214P	2-1/4
5	1-1/4	Easy Roll Donut	Ball	300	7-1/4	4-1/2	6-40-213D	6-41-214D	2-1/4
	1-1/4	Easy Roll Donut	Delrin	300	7-1/4	4-1/2	6-40-214D	6-41-214D	2-1/4
	1-1/4	Easy Roll Flat	Ball	300	7-1/4	4-1/2	6-40-213F	6-41-213F	2-1/4
	1-1/4	Easy Roll Flat	Delrin	300	7-1/4	4-1/2	6-40-214F	6-41-214F	2-1/4
	1-1/4	Polyolefin	Plain	300	7-1/4	4-1/2	6-40-5130	6-41-5130	2-1/4
	1-1/4	Pro-U Grey	Ball	300	7-1/4	4-1/2	6-40-213P	6-41-213P	2-1/4
	1-1/4	Pro-U Grey	Delrin	300	7-1/4	4-1/2	6-40-214P	6-41-214P	2-1/4
	1-1/4	Easy Roll Donut	Ball	300	7-1/4	4-1/2	6-40-213D	6-41-214D	2-1/4
6	1-1/4	Easy Roll Donut	Delrin	300	7-1/4	4-1/2	6-40-214D	6-41-214D	2-1/4
	1-1/4	Easy Roll Flat	Ball	300	7-1/4	4-1/2	6-40-213F	6-41-213F	2-1/4
	1-1/4	Easy Roll Flat	Delrin	300	7-1/4	4-1/2	6-40-214F	6-41-214F	2-1/4
	1-1/4	Polyolefin	Plain	300	7-1/4	4-1/2	6-40-5130	6-41-5130	2-1/4

MEDIUM DUTY CASTERS

44 Series Zinc
445 Series Nickel

FEATURES:

1. **Finish-**
Bright zinc plating or
Bright nickel plating.
2. **Swivel-**
Double ball bearing with
hardened raceways for extra
strength.
3. **Dust Cover-**
Helps protect swivel bearings.
4. **Construction-**
Heavy duty gauge steel formed
for extra strength.
5. **Axle-**
3/8" dia. bolt with lock nut.
6. **Brake-**
Both Top Lock Brake and Maxi
Lock Brake are available.

Note:

Other stem sizes are available on
special request.

WHEELS:



BRAKES:



5-44-213P-41 Zinc
5-445-213P-41 Nickel
Standard Stems

STANDARD SPRING RING STEM SIZES	
Round Stem Number	Dimensions
41	.845 × 2-3/16
42	7/16 × 1-3/8
47	.865 × 2-3/16 with 2 c-rings



5-44-213P-61 Zinc
5-445-213P-61 Nickel
Standard Stems

STANDARD SPRING RING STEM SIZES	
Square Stem Number	Dimensions
61	.860 × 2-3/16
62	.870 × 2-17/32

Dia. Ins.	Wheel			Cap. Pounds	Load Height Ins.	Swivel Radius Ins.	44 Series Spring Ring Stem Catalog No.	App. Wgt. Pounds
	TW Ins.	TYPE	Brg.					
3	1-1/4	Pro-U Grey	Ball	250	3-15/16	2-7/8	3-44-213P	1-1/2
	1-1/4	Pro-U Grey	Delrin	250	3-15/16	2-7/8	3-44-214P	1-1/2
	1-1/4	Easy Roll Donut	Ball	175	3-15/16	2-7/8	3-44-213D	1-1/2
	1-1/4	Easy Roll Donut	Delrin	175	3-15/16	2-7/8	3-44-214D	1-1/2
	1-1/4	Easy Roll Flat	Ball	200	3-15/16	2-7/8	3-44-213F	1-1/2
	1-1/4	Easy Roll Flat	Delrin	200	3-15/16	2-7/8	3-44-214F	1-1/2
	1-1/4	Polyolefin	Plain	250	3-15/16	2-7/8	3-44-5130	1-1/2
3-1/2	1-1/4	Pro-U Grey	Ball	250	4-7/16	3-1/4	3-1/2-44-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	250	4-7/16	3-1/4	3-1/2-44-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	225	4-7/16	3-1/4	3-1/2-44-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	225	4-7/16	3-1/4	3-1/2-44-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	250	4-7/16	3-1/4	3-1/2-44-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	250	4-7/16	3-1/4	3-1/2-44-214F	1-3/4
	1-1/4	Polyolefin	Plain	250	4-7/16	3-1/4	3-1/2-44-5130	1-3/4
4	1-1/4	Pro-U Grey	Ball	275	4-15/16	3-1/2	4-44-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	275	4-15/16	3-1/2	4-44-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	250	4-15/16	3-1/2	4-44-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	250	4-15/16	3-1/2	4-44-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	275	4-15/16	3-1/2	4-44-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	275	4-15/16	3-1/2	4-44-214F	1-3/4
	1-1/4	Polyolefin	Plain	275	4-15/16	3-1/2	4-44-5130	1-3/4
5	1-1/4	Pro-U Grey	Ball	300	6-1/16	4	5-44-213P	2
	1-1/4	Pro-U Grey	Delrin	300	6-1/16	4	5-44-214P	2
	1-1/4	Easy Roll Donut	Ball	250	6-1/16	4	5-44-213D	2
	1-1/4	Easy Roll Donut	Delrin	250	6-1/16	4	5-44-214D	2
	1-1/4	Easy Roll Flat	Ball	300	6-1/16	4	5-44-213F	2
	1-1/4	Easy Roll Flat	Delrin	300	6-1/16	4	5-44-214F	2
	1-1/4	Polyolefin	Plain	300	6-1/16	4	5-44-5130	2
6	1-1/4	Pro-U Grey	Ball	300	7-1/16	4-1/2	6-44-213P	2-1/4
	1-1/4	Pro-U Grey	Delrin	300	7-1/16	4-1/2	6-44-214P	2-1/4
	1-1/4	Easy Roll Donut	Ball	300	7-1/16	4-1/2	6-44-213D	2-1/4
	1-1/4	Easy Roll Donut	Delrin	300	7-1/16	4-1/2	6-44-214D	2-1/4
	1-1/4	Easy Roll Flat	Ball	300	7-1/16	4-1/2	6-44-213F	2-1/4
	1-1/4	Easy Roll Flat	Delrin	300	7-1/16	4-1/2	6-44-214F	2-1/4
	1-1/4	Polyolefin	Plain	300	7-1/16	4-1/2	6-44-5130	2-1/4

MEDIUM DUTY CASTERS

45 Series Zinc
455 Series Nickel

FEATURES:

- 1. Finish-**
Bright zinc plating or
Bright nickel plating.
- 2. Rigid-**
Heavy duty gauge steel pressed
to form for extra strength. Round
or square stems are available.
- 3. Construction-**
Heavy duty gauge steel formed
for extra strength.
- 4. Axle-**
3/8" dia. bolt with lock nut.

Note:

Other stem sizes are available on
special request.

WHEELS:



5-45-5130-47 Zinc
5-455-5130-47 Nickel
Standard Stems

STANDARD SPRING RING STEM SIZES	
Round Stem Number	Dimensions
41	.845 × 2-3/16
47	.865 × 2-3/16 with 2 c-rings



5-45-214P-61 Zinc
5-455-214P-61 Nickel
Standard Stems

STANDARD SPRING RING STEM SIZES	
Square Stem Number	Dimensions
61	.860 × 2-3/16
62	.870 × 2-17/32

Dia.	Wheel			Cap.	Load Height	45 Series Spring Ring Stem	App. Wgt.
	TW	TYPE	Brg.				
Ins.	Ins.			Pounds	Ins.	Catalog No.	Pounds
3	1-1/4	Pro-U Grey	Ball	250	3-15/16	3-45-213P	1-1/2
	1-1/4	Pro-U Grey	Delrin	250	3-15/16	3-45-214P	1-1/2
	1-1/4	Easy Roll Donut	Ball	175	3-15/16	3-45-213D	1-1/2
	1-1/4	Easy Roll Donut	Delrin	175	3-15/16	3-45-214D	1-1/2
	1-1/4	Easy Roll Flat	Ball	200	3-15/16	3-45-213F	1-1/2
	1-1/4	Easy Roll Flat	Delrin	200	3-15/16	3-45-214F	1-1/2
	1-1/4	Polyolefin	Plain	250	3-15/16	3-45-5130	1-1/2
3-1/2	1-1/4	Pro-U Grey	Ball	250	4-7/16	3-1/2-45-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	250	4-7/16	3-1/2-45-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	225	4-7/16	3-1/2-45-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	225	4-7/16	3-1/2-45-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	250	4-7/16	3-1/2-45-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	250	4-7/16	3-1/2-45-214F	1-3/4
	1-1/4	Polyolefin	Plain	250	4-7/16	3-1/2-45-5130	1-3/4
4	1-1/4	Pro-U Grey	Ball	275	4-15/16	4-45-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	275	4-15/16	4-45-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	250	4-15/16	4-45-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	250	4-15/16	4-45-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	275	4-15/16	4-45-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	275	4-15/16	4-45-214F	1-3/4
	1-1/4	Polyolefin	Plain	275	4-15/16	4-45-5130	1-3/4
5	1-1/4	Pro-U Grey	Ball	300	6-1/16	5-45-213P	2
	1-1/4	Pro-U Grey	Delrin	300	6-1/16	5-45-214P	2
	1-1/4	Easy Roll Donut	Ball	250	6-1/16	5-45-213D	2
	1-1/4	Easy Roll Donut	Delrin	250	6-1/16	5-45-214D	2
	1-1/4	Easy Roll Flat	Ball	300	6-1/16	5-45-213F	2
	1-1/4	Easy Roll Flat	Delrin	300	6-1/16	5-45-214F	2
	1-1/4	Polyolefin	Plain	300	6-1/16	5-45-5130	2
6	1-1/4	Pro-U Grey	Ball	300	7-1/16	6-45-213P	2-1/4
	1-1/4	Pro-U Grey	Delrin	300	7-1/16	6-45-214P	2-1/4
	1-1/4	Easy Roll Donut	Ball	300	7-1/16	6-45-213D	2-1/4
	1-1/4	Easy Roll Donut	Delrin	300	7-1/16	6-45-214D	2-1/4
	1-1/4	Easy Roll Flat	Ball	300	7-1/16	6-45-213F	2-1/4
	1-1/4	Easy Roll Flat	Delrin	300	7-1/16	6-45-214F	2-1/4
	1-1/4	Polyolefin	Plain	300	7-1/16	6-45-5130	2-1/4

MEDIUM DUTY CASTERS

46,49 Series
465,495 Series

Zinc
Nickel

FEATURES:

- 1. Finish-**
Bright zinc plating or
Bright nickel plating.
- 2. Swivel-**
Double ball bearing with
hardened raceways for extra
strength.
- 3. Dust Cover-**
Helps protect swivel bearings.
- 4. Construction-**
Heavy duty gauge steel formed
for extra strength.
- 5. Axle-**
3/8" dia. bolt with lock nut.
- 6. Brake-**
Both Top Lock Brake and Maxi
Lock Brake are available.

Note:
Other stem sizes are available on
special request.

WHEELS:



BRAKES:



5-46-213P-22 Zinc
5-465-213P-22 Nickel
Standard Stems

Other stem sizes are available
on special request

STANDARD THREADED STEM SIZES	
Threaded Stem Number	Dimensions
20	1/2 - 13 × 3/4
21	1/2 - 13 × 1
22	1/2 - 13 × 1-1/2
23	1/2 - 13 × 2-3/4
31	5/8 - 11 × 1-3/4
32	3/4 - 10 × 1
33	5/8 - 11 × 1



5-49-5130-50 Zinc
5-495-5130-50 Nickel

Supplied with hollow kingpin for
mounting with 3/8" bolt and nut.

Dia.	Wheel			Cap.	Load Height	Swivel Radius	46 Series	49 Series	App. Wgt.
	TW	TYPE	Brg.				Threaded Stem	Stemless	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
1-1/4	Pro-U Grey	Ball	250	3-15/16	2-7/8	3-46-213P	3-49-213P	1-1/4	
1-1/4	Pro-U Grey	Delrin	250	3-15/16	2-7/8	3-46-214P	3-49-214P	1-1/4	
1-1/4	Easy Roll Donut	Ball	175	3-15/16	2-7/8	3-46-213D	3-49-213D	1-1/4	
3	1-1/4	Easy Roll Donut	Delrin	175	3-15/16	2-7/8	3-46-214D	3-49-214D	1-1/4
1-1/4	Easy Roll Flat	Ball	200	3-15/16	2-7/8	3-46-213F	3-49-213F	1-1/4	
1-1/4	Easy Roll Flat	Delrin	200	3-15/16	2-7/8	3-46-214F	3-49-214F	1-1/4	
1-1/4	Polyolefin	Plain	250	3-15/16	2-7/8	3-46-5130	3-49-5130	1-1/4	
1-1/4	Pro-U Grey	Ball	250	4-7/16	3-1/4	3-1/2-46-213P	3-1/2-49-213P	1-1/2	
1-1/4	Pro-U Grey	Delrin	250	4-7/16	3-1/4	3-1/2-46-214P	3-1/2-49-214P	1-1/2	
1-1/4	Easy Roll Donut	Ball	225	4-7/16	3-1/4	3-1/2-46-213D	3-1/2-49-213D	1-1/2	
3-1/2	1-1/4	Easy Roll Donut	Delrin	225	4-7/16	3-1/4	3-1/2-46-214D	3-1/2-49-214D	1-1/2
1-1/4	Easy Roll Flat	Ball	250	4-7/16	3-1/4	3-1/2-46-213F	3-1/2-49-213F	1-1/2	
1-1/4	Easy Roll Flat	Delrin	250	4-7/16	3-1/4	3-1/2-46-214F	3-1/2-49-214F	1-1/2	
1-1/4	Polyolefin	Plain	250	4-7/16	3-1/4	3-1/2-46-5130	3-1/2-49-5130	1-1/2	
1-1/4	Pro-U Grey	Ball	275	4-15/16	3-1/2	4-46-213P	4-49-213P	1-1/2	
1-1/4	Pro-U Grey	Delrin	275	4-15/16	3-1/2	4-46-214P	4-49-214P	1-1/2	
1-1/4	Easy Roll Donut	Ball	250	4-15/16	3-1/2	4-46-213D	4-49-213D	1-1/2	
4	1-1/4	Easy Roll Donut	Delrin	250	4-15/16	3-1/2	4-46-214D	4-49-214D	1-1/2
1-1/4	Easy Roll Flat	Ball	275	4-15/16	3-1/2	4-46-213F	4-49-213F	1-1/2	
1-1/4	Easy Roll Flat	Delrin	275	4-15/16	3-1/2	4-46-214F	4-49-214F	1-1/2	
1-1/4	Polyolefin	Plain	275	4-15/16	3-1/2	4-46-5130	4-49-5130	1-1/2	
1-1/4	Pro-U Grey	Ball	300	6-1/16	4	5-46-213P	5-49-213P	1-3/4	
1-1/4	Pro-U Grey	Delrin	300	6-1/16	4	5-46-214P	5-49-214P	1-3/4	
1-1/4	Easy Roll Donut	Ball	250	6-1/16	4	5-46-213D	5-49-213D	1-3/4	
5	1-1/4	Easy Roll Donut	Delrin	250	6-1/16	4	5-46-214D	5-49-214D	1-3/4
1-1/4	Easy Roll Flat	Ball	300	6-1/16	4	5-46-213F	5-49-213F	1-3/4	
1-1/4	Easy Roll Flat	Delrin	300	6-1/16	4	5-46-214F	5-49-214F	1-3/4	
1-1/4	Polyolefin	Plain	300	6-1/16	4	5-46-5130	5-49-5130	1-3/4	
1-1/4	Pro-U Grey	Ball	300	7-1/16	4-1/2	6-46-213P	6-49-213P	2	
1-1/4	Pro-U Grey	Delrin	300	7-1/16	4-1/2	6-46-214P	6-49-214P	2	
1-1/4	Easy Roll Donut	Ball	300	7-1/16	4-1/2	6-46-213D	6-49-213D	2	
6	1-1/4	Easy Roll Donut	Delrin	300	7-1/16	4-1/2	6-46-214D	6-49-214D	2
1-1/4	Easy Roll Flat	Ball	300	7-1/16	4-1/2	6-46-213F	6-49-213F	2	
1-1/4	Easy Roll Flat	Delrin	300	7-1/16	4-1/2	6-46-214F	6-49-214F	2	
1-1/4	Polyolefin	Plain	300	7-1/16	4-1/2	6-46-5130	6-49-5130	2	

MEDIUM DUTY CASTERS

50 Series Zinc
505 Series Nickel



FEATURES:

- 1. Finish-**
Bright zinc plating or
Bright nickel plating.
- 2. Swivel-**
Double ball bearing with
hardened raceways for extra
strength.
- 3. Dust Cover-**
Helps protect swivel bearings.
- 4. Construction-**
Heavy duty gauge steel formed
for extra strength.
- 5. Axle-**
3/8" dia. bolt with lock nut.
- 6. Brake-**
Both Top Lock Brake and Maxi
Lock Brake are available.
- 7. Applicator-**
Fits a wide range of tubing from
7/8" I.D. to 1-7/8" I.D., round or
square. Please specify exact
tubing I.D. or O.D. and gauge.



5-50-213P-19 Zinc
5-505-213P-19 Nickel

WHEELS:



BRAKES:



EXPANDING RUBBER APPLICATOR SIZES						
Applicator Number	Tubing ID (Inches)	Size Range (Inches)	Knurled Nut	Expanding Rubber	Plain Bushing	Base Washer
11	7/8	0.852-0.927	1435-02	1645-00	1432-00	1473-02
15	1-1/8	1.030-1.140	1436-02	1646-00	1433-00	1473-02
17	1-3/16	1.178-1.303	1441-02	1648-00	1430-00	1473-02
19C	1-3/8	1.360-1.425	1438-02	1647-00	1436-00	1473-02
19A	1-1/2	1.426-1.589	1437-02	1649-00	1434-00	1473-02
21	1-7/8	1.790-1.850	1422-02	1650-00	1440-00	1473-02

Dia. Ins.	Wheel			Cap. Pounds	Load Height Ins.	Swivel Radius Ins.	50 Series Applicator Catalog No.	App. Wgt. Pounds
	TW Ins.	TYPE	Brg.					
3	1-1/4	Pro-U Grey	Ball	250	3-15/16	2-7/8	3-50-213P	1-1/2
	1-1/4	Pro-U Grey	Delrin	250	3-15/16	2-7/8	3-50-214P	1-1/2
	1-1/4	Easy Roll Donut	Ball	175	3-15/16	2-7/8	3-50-213D	1-1/2
	1-1/4	Easy Roll Donut	Delrin	175	3-15/16	2-7/8	3-50-214D	1-1/2
	1-1/4	Easy Roll Flat	Ball	200	3-15/16	2-7/8	3-50-213F	1-1/2
	1-1/4	Easy Roll Flat	Delrin	200	3-15/16	2-7/8	3-50-214F	1-1/2
	1-1/4	Polyolefin	Plain	250	3-15/16	2-7/8	3-50-5130	1-1/2
3 1/2	1-1/4	Pro-U Grey	Ball	250	4-7/16	3-1/4	3-1/2-50-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	250	4-7/16	3-1/4	3-1/2-50-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	225	4-7/16	3-1/4	3-1/2-50-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	225	4-7/16	3-1/4	3-1/2-50-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	250	4-7/16	3-1/4	3-1/2-50-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	250	4-7/16	3-1/4	3-1/2-50-214F	1-3/4
	1-1/4	Polyolefin	Plain	250	4-7/16	3-1/4	3-1/2-50-5130	1-3/4
4	1-1/4	Pro-U Grey	Ball	275	4-15/16	3-1/2	4-50-213P	1-3/4
	1-1/4	Pro-U Grey	Delrin	275	4-15/16	3-1/2	4-50-214P	1-3/4
	1-1/4	Easy Roll Donut	Ball	250	4-15/16	3-1/2	4-50-213D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	250	4-15/16	3-1/2	4-50-214D	1-3/4
	1-1/4	Easy Roll Flat	Ball	275	4-15/16	3-1/2	4-50-213F	1-3/4
	1-1/4	Easy Roll Flat	Delrin	275	4-15/16	3-1/2	4-50-214F	1-3/4
	1-1/4	Polyolefin	Plain	275	4-15/16	3-1/2	4-50-5130	1-3/4
5	1-1/4	Pro-U Grey	Ball	300	6-1/16	4	5-50-213P	2
	1-1/4	Pro-U Grey	Delrin	300	6-1/16	4	5-50-214P	2
	1-1/4	Easy Roll Donut	Ball	250	6-1/16	4	5-50-213D	2
	1-1/4	Easy Roll Donut	Delrin	250	6-1/16	4	5-50-214D	2
	1-1/4	Easy Roll Flat	Ball	300	6-1/16	4	5-50-213F	2
	1-1/4	Easy Roll Flat	Delrin	300	6-1/16	4	5-50-214F	2
	1-1/4	Polyolefin	Plain	300	6-1/16	4	5-50-5130	2
6	1-1/4	Pro-U Grey	Ball	300	7-1/16	4-1/2	6-50-213P	2-1/4
	1-1/4	Pro-U Grey	Delrin	300	7-1/16	4-1/2	6-50-214P	2-1/4
	1-1/4	Easy Roll Donut	Ball	300	7-1/16	4-1/2	6-50-213D	2-1/4
	1-1/4	Easy Roll Donut	Delrin	300	7-1/16	4-1/2	6-50-214D	2-1/4
	1-1/4	Easy Roll Flat	Ball	300	7-1/16	4-1/2	6-50-213F	2-1/4
	1-1/4	Easy Roll Flat	Delrin	300	7-1/16	4-1/2	6-50-214F	2-1/4
	1-1/4	Polyolefin	Plain	300	7-1/16	4-1/2	6-50-5130	2-1/4