

MEDIUM HEAVY DUTY CASTERS

51,52 Series Zinc

FEATURES:

1. **Finish-**
Bright zinc plating.
2. **Swivel-**
Double ball bearing with hardened raceways for extra strength.
3. **Rigid-**
Welded with heavy duty gauge steel for extra strength.
4. **Dust Cover-**
For all swivel models. Helps protect bearings for greater performance.
5. **Construction-**
Made of heavy duty gauge steel and heat treated for extra strength.
6. **Axle-**
3/8" dia. bolt with lock nut for 3", 4" and 5"; 1/2" dia. bolt with lock nut for 6" and 8".
7. **Brake-**
Top Lock Brake is available for swivel.
8. **King Pin-**
1/2" steel rivet hydraulically upset.
9. **Fork Leg Spacing- 2"**
10. **Grease Seal- Optional**

WHEELS:



BRAKES:



Business Machine

3-51-5520-2 Zinc
Available only in 3"



5-51-250F-2 Zinc

STANDARD TOP PLATE SIZES			
Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8



5-52-250P-5 Zinc

STANDARD TOP PLATE SIZES			
Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-1/2 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8

Wheel				Cap. Pounds	Load Height Ins.	Swivel Radius Ins.	51 Series Swivel Plate	52 Series Rigid Plate	App. Wgt. Pounds
Dia.	TW	TYPE	Brg.				Catalog No.	Catalog No.	
3	1-13/16	Polyolefin	Roller	400	4	2-3/8	3-51-5520	3-52-5520	1-3/4
4	1-1/2	Polyolefin	Roller	375	5-3/8	3-1/2	4-51-5220	4-52-5220	2-1/8
	1-1/2	Easy Roll Flat	Roller	400	6-1/4	4	5-51-250F	5-52-250F	2-1/8
5	1-1/2	Pro-U Grey	Roller	400	6-1/4	4	5-51-250P	5-52-250P	2-1/8
	1-1/2	Polyolefin	Roller	400	6-1/4	4	5-51-5220	5-52-5220	2-3/4
	1-1/2	Easy Roll Flat	Roller	400	7-1/2	4-3/4	6-51-250F	6-52-250F	2-3/4
6	1-1/2	Pro-U Grey	Roller	400	7-1/2	4-3/4	6-51-250P	6-52-250P	2-3/4
	1-1/2	Polyolefin	Roller	400	7-1/2	4-3/4	6-51-5220	6-52-5220	2-3/4