

# PNEUMATIC/ FOAM FILLED CASTERS

90,91 Series Zinc



10-90-254G-1 Zinc  
10-90-25FG-1 Zinc

Pneumatic/ Foam Filled Swivel

## STANDARD TOP PLATE SIZE

Topl Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
1	4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8



10-91-254B-1 Zinc  
10-91-25FB-1 Zinc

Pneumatic/ Foam Filled Rigid

## STANDARD TOP PLATE SIZE

Topl Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
1	4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8

## FEATURES:

- 1. Finish-**  
Bright zinc plating.
- 2. Swivel-**  
Double ball bearing with hardened raceways for extra strength.
- 3. Top Lock Brake-**  
Available for swivel caster.
- 4. Large foot pedal-**  
Makes brake easier to operate and provides better foot placement.
- 5. All wheels are with 3 piece steel hub.**

## WHEELS:



## BRAKES:



Wheel				Load			90 Series	91 Series	App. Wgt.
Dia. TW		TYPE	Brg.	Cap.	Height	Offset	Swivel Plate	Rigid Plate	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
6	2	Pneumatic	Ball	265	7-1/2	2-1/16	6-90-254G	6-91-254G	5
	2	Pneumatic	Ball	265	7-1/2	2-1/16	6-90-254B	6-91-254B	5
	2	Foam Filled	Ball	350	7-1/2	2-1/16	6-90-25FG	6-91-25FG	5-3/4
	2	Foam Filled	Ball	350	7-1/2	2-1/16	6-90-25FB	6-91-25FB	5-3/4
8	2-1/2	Pneumatic	Ball	310	10	2-3/4	8-90-254G	8-91-254G	7-1/4
	2-1/2	Pneumatic	Ball	310	10	2-3/4	8-90-254B	8-91-254B	7-1/4
	2-1/2	Foam Filled	Ball	450	10	2-3/4	8-90-25FG	8-91-25FG	8-1/4
	2-1/2	Foam Filled	Ball	450	10	2-3/4	8-90-25FB	8-91-25FB	8-1/4
10	3-1/2	Pneumatic	Ball	350	11-7/8	2-5/8	10-90-354G	10-91-354G	8-3/4
	3-1/2	Pneumatic	Ball	350	11-7/8	2-5/8	10-90-354B	10-91-354B	8-3/4
	3-1/2	Foam Filled	Ball	550	11-7/8	2-5/8	10-90-35FG	10-91-35FG	11
	3-1/2	Foam Filled	Ball	550	11-7/8	2-5/8	10-90-35FB	10-91-35FB	11