

# PROFESSIONAL CASTERS

P0,P4,P6 Series  
P05,P45,P65 Series  
P0S,P4S,P6S Series

Zinc  
Nickel  
Stainless

## FEATURES:

Professional Lock casters are used on food service and utility carts as well as hospital equipment.

### Easy Step: ON/OFF

Professional Lock either locks the swivel and wheel making the unit stationary, or locks the swivel in a straight tracking position. Pedals are ergonomically designed for better access.

- 1. Finish-** Bright zinc plating or Bright nickel plating.
- 2. Swivel-** Double ball bearing with hardened raceways for extra strength.
- 3. Dust Cover-** Helps protect swivel bearings.
- 4. Construction-** Heavy duty gauge steel formed for extra strength.
- 5. Axle-** 3/8" dia. bolt with lock nut.
- 6. Applicator-** P7, P75, P7S Series Expanding rubber applicator available upon request.
- 7. Grease Seal-** Optional

### WHEELS:



**5-P0-213D-2** Zinc  
**5-P05-213D-2** Nickel

### STANDARD TOP PLATE SIZES

Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8



**5-P4-213D-41** Zinc  
**5-P45-213D-41** Nickel

### STANDARD SPRING RING STEM SIZES

Round Stem Number	Dimensions
41	.845 × 2-3/16
47	.865 × 2-3/16 with 2 c-rings
61	.860 × 2-3/16



**5-P6-213D-22** Zinc  
**5-P65-213D-22** Nickel

### STANDARD THREADED STEM SIZES

Threaded Stem Number	Dimensions
20	1/2 - 13 × 3/4
21	1/2 - 13 × 1
22	1/2 - 13 × 1-1/2
23	1/2 - 13 × 2-3/4
31	5/8 - 11 × 1-3/4
32	3/4 - 10 × 1
33	5/8 - 11 × 1

Dia.	Wheel			Cap.	Load Height	Swivel Radius	P0 Series	P6 Series	App. Wgt.
	TW	TYPE	Brg.				Swivel Plate	Threaded Stem	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
4	1-1/4	Pro-U Grey	Ball	275	5-1/8	4-3/8	4-P0-213P	4-P6-213P	2
	1-1/4	Pro-U Grey	Delrin	275	5-1/8	4-3/8	4-P0-214P	4-P6-214P	2
	1-1/4	Easy Roll Donut	Ball	250	5-1/8	4-3/8	4-P0-213D	4-P6-213D	2
	1-1/4	Easy Roll Donut	Delrin	250	5-1/8	4-3/8	4-P0-214D	4-P6-214D	2
	1-1/4	Easy Roll Flat	Ball	275	5-1/8	4-3/8	4-P0-213F	4-P6-213F	2
	1-1/4	Easy Roll Flat	Delrin	275	5-1/8	4-3/8	4-P0-214F	4-P6-214F	2
5	1-1/4	Pro-U Grey	Ball	300	6-1/4	4-7/16	5-P0-213P	5-P6-213P	2-1/2
	1-1/4	Pro-U Grey	Delrin	300	6-1/4	4-7/16	5-P0-214P	5-P6-214P	2-1/2
	1-1/4	Easy Roll Donut	Ball	250	6-1/4	4-7/16	5-P0-213D	5-P6-213D	2-1/2
	1-1/4	Easy Roll Donut	Delrin	250	6-1/4	4-7/16	5-P0-214D	5-P6-214D	2-1/2
	1-1/4	Easy Roll Flat	Ball	300	6-1/4	4-7/16	5-P0-213F	5-P6-213F	2-1/2
	1-1/4	Easy Roll Flat	Delrin	300	6-1/4	4-7/16	5-P0-214F	5-P6-214F	2-1/2
6	1-1/4	Pro-U Grey	Ball	300	7-1/4	4-1/2	6-P0-213P	6-P6-213P	2-3/4
	1-1/4	Pro-U Grey	Delrin	300	7-1/4	4-1/2	6-P0-214P	6-P6-214P	2-3/4
	1-1/4	Easy Roll Donut	Ball	300	7-1/4	4-1/2	6-P0-213D	6-P6-213D	2-3/4
	1-1/4	Easy Roll Donut	Delrin	300	7-1/4	4-1/2	6-P0-214D	6-P6-214D	2-3/4
	1-1/4	Easy Roll Flat	Ball	300	7-1/4	4-1/2	6-P0-213F	6-P6-213F	2-3/4
	1-1/4	Easy Roll Flat	Delrin	300	7-1/4	4-1/2	6-P0-214F	6-P6-214F	2-3/4

Note: Deduct 3/16" from load height for all stem casters.