

# SHOCK ABSORBING CASTERS

Z0, Z1 Series  
Z05, Z15 Series

Zinc  
Nickel

## FEATURES:

1. **Finish-**  
Bright zinc plating or Bright nickel plating.
2. **Swivel-**  
Double ball bearing with hardened raceways for extra strength.
3. **Rigid-**  
Pressed with heavy duty gauge steel for extra strength.
4. **Dust Cover-**  
Helps protect swivel bearings.
5. **Construction-** Heavy duty gauge steel formed for extra strength.
6. **Axle-** 3/8" dia. bolt with zerk and lock nut.
7. **Brake-** Maxi Lock available.

## Note:

1. Other wheels are available on special request.
2. Available directly from Vulcan Machinery.

## WHEELS:



## BRAKES:



5-Z0-213P-2 Zinc  
5-Z05-213P-2 Nickel

### STANDARD TOP PLATE SIZES FOR SWIVEL

Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8

Other plate sizes are available on special request.



5-Z1-213P-2 Zinc  
5-Z15-213P-2 Nickel

#2 Top Plate available only.

Wheel				Cap. Pounds	Load Height Ins.	Swivel Radius Ins.	Cone Spring Φ	Z0 Series	Z1 Series	App. Wgt. Pounds
Dia.	TW	TYPE	Brg.					Swivel	Rigid	
Ins.	Ins.							Catalog No.	Catalog No.	
4	1-1/4	Easy Roll Donut	Ball	68	5-7/8~6-1/6	4~4-1/8	1/8	4-Z0-213D	4-Z1-213D	3
	1-1/4	Easy Roll Donut	Delrin	68	5-7/8~6-1/6	4~4-1/8	1/8	4-Z0-214D	4-Z1-214D	3
	1-1/4	Easy Roll Flat	Ball	68	5-7/8~6-1/6	4~4-1/8	1/8	4-Z0-213F	4-Z1-213F	3
	1-1/4	Easy Roll Flat	Delrin	68	5-7/8~6-1/6	4~4-1/8	1/8	4-Z0-214F	4-Z1-214F	3