

# TOTAL/ DIRECTO LOCK CASTERS

72,74 Series  
72S,74S Series

Zinc  
Stainless

### FEATURES:

Casters with Total Lock or Directo Lock used for food service, utility carts, health care and hospital equipment.

### Easy Step: ON/OFF

**Total Lock:**  
Simultaneously locks the swivel and wheel making the unit stationary.

**Directo Lock:**  
Locks the swivel in straight tracking position.

1. **Finish-**  
Bright zinc plating.
2. **Swivel-**  
Double ball bearing with hardened raceways for extra strength.
3. **Dust Cover-**  
Helps protect swivel bearings.
4. **Construction-**  
Heavy duty gauge steel formed for extra strength.
5. **Axle-**  
3/8" dia. bolt with lock nut.
6. **Grease Seal- Optional**

### WHEELS:



5-72-213P-2 Zinc

STANDARD TOP PLATE SIZE			
Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16



5-74-213P-41 Zinc

STANDARD SPRING RING STEM SIZES	
Stem Number	Dimensions
41	.845 × 2-3/16
47	.865 × 2-3/16 with 2 c-rings
61	.860 × 2-3/16

Dia.	Wheel			Cap.	Load Height	Swivel Radius	72 Series	74 Series	App. Wgt.
	TW	TYPE	Brg.				Total/Directo	Total/Directo	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
3	1-1/4	Pro-U Grey	Ball	250	4-1/8	4-3/16	3-72-213P-T/D	3-74-213P-T/D	1-3/4
	1-1/4	Pro-U Grey	Delrin	250	4-1/8	4-3/16	3-72-214P-T/D	3-74-214P-T/D	1-3/4
	1-1/4	Easy Roll Donut	Ball	175	4-1/8	4-3/16	3-72-213D-T/D	3-74-213D-T/D	1-3/4
	1-1/4	Easy Roll Donut	Delrin	175	4-1/8	4-3/16	3-72-214D-T/D	3-74-214D-T/D	1-3/4
	1-1/4	Easy Roll Flat	Ball	200	4-1/8	4-3/16	3-72-213F-T/D	3-74-213F-T/D	1-3/4
	1-1/4	Easy Roll Flat	Delrin	200	4-1/8	4-3/16	3-72-214F-T/D	3-74-214F-T/D	1-3/4
	1-1/4	Polyolefin	Plain	250	4-1/8	4-3/16	3-72-5130-T/D	3-74-5130-T/D	1-3/4
	1-1/4	Pro-U Grey	Ball	275	5-1/8	4-3/16	4-72-213P-T/D	4-74-213P-T/D	2
4	1-1/4	Pro-U Grey	Delrin	275	5-1/8	4-3/16	4-72-214P-T/D	4-74-214P-T/D	2
	1-1/4	Easy Roll Donut	Ball	250	5-1/8	4-3/16	4-72-213D-T/D	4-74-213D-T/D	2
	1-1/4	Easy Roll Donut	Delrin	250	5-1/8	4-3/16	4-72-214D-T/D	4-74-214D-T/D	2
	1-1/4	Easy Roll Flat	Ball	275	5-1/8	4-3/16	4-72-213F-T/D	4-74-213F-T/D	2
	1-1/4	Easy Roll Flat	Delrin	275	5-1/8	4-3/16	4-72-214F-T/D	4-74-214F-T/D	2
	1-1/4	Polyolefin	Plain	275	5-1/8	4-3/16	4-72-5130-T/D	4-74-5130-T/D	2
	1-1/4	Pro-U Grey	Ball	300	6-1/4	4-3/16	5-72-213P-T/D	5-74-213P-T/D	2-1/4
	1-1/4	Pro-U Grey	Delrin	300	6-1/4	4-3/16	5-72-214P-T/D	5-74-214P-T/D	2-1/4
5	1-1/4	Easy Roll Donut	Ball	250	6-1/4	4-3/16	5-72-213D-T/D	5-74-213D-T/D	2-1/4
	1-1/4	Easy Roll Donut	Delrin	250	6-1/4	4-3/16	5-72-214D-T/D	5-74-214D-T/D	2-1/4
	1-1/4	Easy Roll Flat	Ball	300	6-1/4	4-3/16	5-72-213F-T/D	5-74-213F-T/D	2-1/4
	1-1/4	Easy Roll Flat	Delrin	300	6-1/4	4-3/16	5-72-214F-T/D	5-74-214F-T/D	2-1/4
	1-1/4	Polyolefin	Plain	300	6-1/4	4-3/16	5-72-5130-T/D	5-74-5130-T/D	2-1/4
	1-1/4	Pro-U Grey	Ball	300	7-1/4	4-1/2	6-72-213P-T/D	6-74-213P-T/D	2-1/2
	1-1/4	Pro-U Grey	Delrin	300	7-1/4	4-1/2	6-72-214P-T/D	6-74-214P-T/D	2-1/2
	1-1/4	Easy Roll Donut	Ball	300	7-1/4	4-1/2	6-72-213D-T/D	6-74-213D-T/D	2-1/2
6	1-1/4	Easy Roll Donut	Delrin	300	7-1/4	4-1/2	6-72-214D-T/D	6-74-214D-T/D	2-1/2
	1-1/4	Easy Roll Flat	Ball	300	7-1/4	4-1/2	6-72-213F-T/D	6-74-213F-T/D	2-1/2
	1-1/4	Easy Roll Flat	Delrin	300	7-1/4	4-1/2	6-72-214F-T/D	6-74-214F-T/D	2-1/2
	1-1/4	Easy Roll Flat	Delrin	300	7-1/4	4-1/2	6-72-214F-T/D	6-74-214F-T/D	2-1/2

### Note:

1. When ordering, item numbers with a "D" indicate Directo. When ordering, item numbers with a "T" indicate Total.
2. Deduct 3/16" from load height for all stem casters.

# TOTAL/ DIRECTO LOCK CASTERS

76,77 Series  
76S,77S Series

Zinc  
Stainless

### FEATURES:

Casters with Total Lock or Directo Lock used for food service, utility carts, health care and hospital equipment.

### Easy Step: ON/OFF

**Total Lock:**  
Simultaneously locks the swivel and wheel making the unit stationary.

**Directo Lock:**  
Locks the swivel in straight tracking position.

1. **Finish-**  
Bright zinc plating.
2. **Swivel-**  
Double ball bearing with hardened raceways for extra strength.
3. **Dust Cover-**  
Helps protect swivel bearings.
4. **Construction-**  
Heavy duty gauge steel formed for extra strength.
5. **Axle-**  
3/8" dia. bolt with lock nut.
6. **Grease Seal-** Optional

### WHEELS:



5-76-213P-22 Zinc

STANDARD THREADED STEM SIZES	
Threaded Stem Number	Dimensions
20	1/2 - 13 × 3/4
21	1/2 - 13 × 1
22	1/2 - 13 × 1-1/2
23	1/2 - 13 × 2-3/4
31	5/8 - 11 × 1-3/4
32	3/4 - 10 × 1
33	5/8 - 11 × 1



5-77-213P-19 Zinc

EXPANDING RUBBER APPLICATOR SIZES						
Applicator Number	Tubing ID (inches)	Size Range (inches)	Knurled Nut	Expanding Rubber	Plain Bushing	Base Washer
11	7/8	0.852-0.927	1435-02	1645-00	1432-00	1473-02
15	1-1/8	1.030-1.140	1436-02	1646-00	1433-00	1473-02
17	1-3/16	1.178-1.303	1441-02	1648-00	1430-00	1473-02
19C	1-3/8	1.360-1.425	1438-02	1647-00	1436-00	1473-02
19A	1-1/2	1.426-1.589	1437-02	1649-00	1434-00	1473-02
21	1-7/8	1.790-1.850	1422-02	1650-00	1440-00	1473-02

Dia.	Wheel			Cap.	Load Height	Swivel Radius	76 Series	77 Series	App. Wgt.
	TW	TYPE	Brg.				Total/Directo	Total	
Ins.	Ins.			Pounds	Ins.	Ins.	Catalog No.	Catalog No.	Pounds
1-1/4	Pro-U Grey	Ball	250	3-15/16	4-3/16	3-76-213P-T/D	3-77-213P-T	1-3/4	
1-1/4	Pro-U Grey	Delrin	250	3-15/16	4-3/16	3-76-214P-T/D	3-77-214P-T	1-3/4	
1-1/4	Easy Roll Donut	Ball	175	3-15/16	4-3/16	3-76-213D-T/D	3-77-213D-T	1-3/4	
3	1-1/4	Easy Roll Donut	Delrin	175	3-15/16	4-3/16	3-76-214D-T/D	3-77-214D-T	1-3/4
1-1/4	Easy Roll Flat	Ball	200	3-15/16	4-3/16	3-76-213F-T/D	3-77-213F-T	1-3/4	
1-1/4	Easy Roll Flat	Delrin	200	3-15/16	4-3/16	3-76-214F-T/D	3-77-214F-T	1-3/4	
1-1/4	Polyolefin	Plain	250	3-15/16	4-3/16	3-76-5130-T/D	3-77-5130-T	1-3/4	
1-1/4	Pro-U Grey	Ball	275	4-15/16	4-3/16	4-76-213P-T/D	4-77-213P-T	2	
1-1/4	Pro-U Grey	Delrin	275	4-15/16	4-3/16	4-76-214P-T/D	4-77-214P-T	2	
1-1/4	Easy Roll Donut	Ball	250	4-15/16	4-3/16	4-76-213D-T/D	4-77-213D-T	2	
4	1-1/4	Easy Roll Donut	Delrin	250	4-15/16	4-3/16	4-76-214D-T/D	4-77-214D-T	2
1-1/4	Easy Roll Flat	Ball	275	4-15/16	4-3/16	4-76-213F-T/D	4-77-213F-T	2	
1-1/4	Easy Roll Flat	Delrin	275	4-15/16	4-3/16	4-76-214F-T/D	4-77-214F-T	2	
1-1/4	Polyolefin	Plain	275	4-15/16	4-3/16	4-76-5130-T/D	4-77-5130-T	2	
1-1/4	Pro-U Grey	Ball	300	6-1/16	4-3/16	5-76-213P-T/D	5-77-213P-T	2-1/4	
1-1/4	Pro-U Grey	Delrin	300	6-1/16	4-3/16	5-76-214P-T/D	5-77-214P-T	2-1/4	
1-1/4	Easy Roll Donut	Ball	250	6-1/16	4-3/16	5-76-213D-T/D	5-77-213D-T	2-1/4	
5	1-1/4	Easy Roll Donut	Delrin	250	6-1/16	4-3/16	5-76-214D-T/D	5-77-214D-T	2-1/4
1-1/4	Easy Roll Flat	Ball	300	6-1/16	4-3/16	5-76-213F-T/D	5-77-213F-T	2-1/4	
1-1/4	Easy Roll Flat	Delrin	300	6-1/16	4-3/16	5-76-214F-T/D	5-77-214F-T	2-1/4	
1-1/4	Polyolefin	Plain	300	6-1/16	4-3/16	5-76-5130-T/D	5-77-5130-T	2-1/4	
1-1/4	Pro-U Grey	Ball	300	7-1/16	4-1/2	6-76-213P-T/D	6-77-213P-T	2-1/2	
1-1/4	Pro-U Grey	Delrin	300	7-1/16	4-1/2	6-76-214P-T/D	6-77-214P-T	2-1/2	
1-1/4	Easy Roll Donut	Ball	300	7-1/16	4-1/2	6-76-213D-T/D	6-77-213D-T	2-1/2	
6	1-1/4	Easy Roll Donut	Delrin	300	7-1/16	4-1/2	6-76-214D-T/D	6-77-214D-T	2-1/2
1-1/4	Easy Roll Flat	Ball	300	7-1/16	4-1/2	6-76-213F-T/D	6-77-213F-T	2-1/2	
1-1/4	Easy Roll Flat	Delrin	300	7-1/16	4-1/2	6-76-214F-T/D	6-77-214F-T	2-1/2	

### Note:

1. When ordering, item numbers with a "D" indicate Directo. When ordering, item numbers with a "T" indicate Total.