

TOTAL/ DIRECTIONAL LOCK CASTERS

T0-D0 - T9-D9 Series
T05-D05 - T95-D95 Series

Zinc
Nickel

FEATURES:

These casters are available in both total lock and directional lock. Pedals are ergonomically designed for better access. They are used on food service, utility carts, health care and hospital equipment.

Easy Step: ON/OFF

Total Lock:

Simultaneously locks the swivel and wheel making the unit stationary.

Directional Lock:

Locks the swivel in straight tracking position.

- 1. Finish-** Bright zinc plating or Bright nickel plating.
- 2. Swivel-** Double ball bearing with hardened raceways for extra strength.
- 3. Dust Cover-** Helps protect swivel bearings.
- 4. Construction-** Heavy duty gauge steel formed for extra strength.
- 5. Axle-** 3/8" dia. bolt with lock nut.

WHEELS:



5-T0-213D-2 Zinc
5-T05-213D-2 Nickel

SERIES T0/D0
Standard Top Plate

STANDARD TOP PLATE SIZES

Top Plate Number	Overall Size	Bolt Hole Spacing	Mounting Bolt
2	2-3/8 × 3-5/8	1-3/4 × 3	5/16
3	3-1/8 × 4-1/8	2-3/8 × 3-7/16	5/16
4	3-1/2 × 3-1/2	2-5/8 × 2-5/8 slotted to 2-3/4 × 2-3/4	5/16
5	3-3/4 × 4-1/2	2-5/8 × 3-5/8 slotted to 3 × 3	3/8



5-D4-213D-41 Zinc
5-D45-213D-41 Nickel

SERIES T4/D4

STANDARD SPRING RING STEM SIZES

Round Stem Number	Dimensions
41	.845 × 2-3/16
47	.865 × 2-3/16 with 2 c-rings
61	.860 × 2-3/16



5-T6-213D-22 Zinc
5-T65-213D-22 Nickel

SERIES T6/D6

STANDARD THREADED STEM SIZES

Threaded Stem Number	Dimensions
20	1/2 - 13 × 3/4
21	1/2 - 13 × 1
22	1/2 - 13 × 1-1/2
23	1/2 - 13 × 2-3/4
31	5/8 - 11 × 1-3/4
32	3/4 - 10 × 1
33	5/8 - 11 × 1

Wheel		Cap. Pounds	Load Height Ins.	Swivel Radius Ins.	T0 Series	D0 Series	App. Wgt. Pounds		
Dia.	TW				Total Lock	Directo Lock			
Ins.	Ins.	TYPE	Brg.	Catalog No.	Catalog No.				
1-1/4	Pro-U Grey	Ball	275	5-1/8	5-1/16	4-T0-213P-T	4-D0-213P-D	2	
1-1/4	Pro-U Grey	Delrin	275	5-1/8	5-1/16	4-T0-214P-T	4-D0-214P-D	2	
1-1/4	Easy Roll Donut	Ball	250	5-1/8	5-1/16	4-T0-213D-T	4-D0-213D-D	2	
4	1-1/4	Easy Roll Donut	Delrin	250	5-1/8	5-1/16	4-T0-214D-T	4-D0-214D-D	2
1-1/4	Easy Roll Flat	Ball	275	5-1/8	5-1/16	4-T0-213F-T	4-D0-213F-D	2	
1-1/4	Easy Roll Flat	Delrin	275	5-1/8	5-1/16	4-T0-214F-T	4-D0-214F-D	2	
1-1/4	Polyolefin	Plain	275	5-1/8	5-1/16	4-T0-5130-T	4-D0-5130-D	2	
1-1/4	Pro-U Grey	Ball	300	6-1/4	5-1/16	5-T0-213P-T	5-D0-213P-D	2-1/4	
1-1/4	Pro-U Grey	Delrin	300	6-1/4	5-1/16	5-T0-214P-T	5-D0-214P-D	2-1/4	
1-1/4	Easy Roll Donut	Ball	250	6-1/4	5-1/16	5-T0-213D-T	5-D0-213D-D	2-1/4	
5	1-1/4	Easy Roll Donut	Delrin	250	6-1/4	5-1/16	5-T0-214D-T	5-D0-214D-D	2-1/4
1-1/4	Easy Roll Flat	Ball	300	6-1/4	5-1/16	5-T0-213F-T	5-D0-213F-D	2-1/4	
1-1/4	Easy Roll Flat	Delrin	300	6-1/4	5-1/16	5-T0-214F-T	5-D0-214F-D	2-1/4	
1-1/4	Polyolefin	Plain	300	6-1/4	5-1/16	5-T0-5130-T	5-D0-5130-D	2-1/4	
1-1/4	Pro-U Grey	Ball	300	7-1/4	5-1/8	6-T0-213P-T	6-D0-213P-D	2-1/2	
1-1/4	Pro-U Grey	Delrin	300	7-1/4	5-1/8	6-T0-214P-T	6-D0-214P-D	2-1/2	
6	1-1/4	Easy Roll Donut	Ball	300	7-1/4	5-1/8	6-T0-213D-T	6-D0-213D-D	2-1/2
1-1/4	Easy Roll Donut	Delrin	300	7-1/4	5-1/8	6-T0-214D-T	6-D0-214D-D	2-1/2	
1-1/4	Easy Roll Flat	Ball	300	7-1/4	5-1/8	6-T0-213F-T	6-D0-213F-D	2-1/2	
1-1/4	Easy Roll Flat	Delrin	300	7-1/4	5-1/8	6-T0-214F-T	6-D0-214F-D	2-1/2	

Note:

- When ordering, item numbers with a "D" indicate Directional. When ordering, item numbers with a "T" indicate Total.
- Deduct 3/16" from load height for all stem casters.